



PRODUCT DETAILS

Liner	Cut resistant yarn, thermo yarn, mixed with others
Gauge	15 & 7
Coating	Nitrile
Finishing	Flat
Colour	Blue / Black
Size	7,8,9,10,11
Packing	12 pairs/pack, 120 pairs/carton
Tariff number	61161020

RECOMMENDED APPLICATIONS

Works in cold conditions with / without cut hazards in dry or wet or oily conditions.

Such as outdoor works , cold storage, maintenance, handling sharp or rough edge parts, machine operation, logistics, warehouse works and etc.



CERTIFICATION

 EN21420:2020

Category II

**EN388:2016 Mechanical protection:
levels obtained in laboratory tests**

Abrasion (min.0 to max. 4):

EN388:2016



Blade cut - coupe test (Index) (min.0 to max. 5):

4

Tear (min.0 to max. 4):

X

Puncture (min.0 to max. 4):

2

Cut resistance from sharp objects EN ISO

2

13997:1999 (min. A to max. F, X - not tested):

C

Impact protection (P if pass, F if failed):

-

EN21420:2020 Dexterity (min.0 to max.5):

level 5.

**EN511:2006 Cold protection:
levels obtained in laboratory tests**

A - Convective cold: min.0 to max. 4
B - Contact cold: min.0 to max. 4
C - Water penetration: (1 if pass, 0 if failed)

EN511:2006



X = not tested or testing method is unsuitable for the design of the gloves.

STORAGE AND SHELF LIFE

Please store the products in original packing in a dry and cool place without direct sunlight in general. The shelf life depends on the storage and other conditions. For the new product stored in a properly way, the shelf life of Xcellent 51-900 can normally be 5 years.

CLEANING

Washing or dry-cleaning requires prior consultation with a recognized specialist, because such treatment may alter the protective properties of the glove. The gloves must always be checked for integrity before reuse. The rating with the marked performance levels based on tests on unused gloves.

WARNING

Don't use in case of chemicals or electrical risk.

Please ensure the products are strictly used within their protection levels.

